

AIRFLOW
 3000


AIRFLOW 3000

JET-AIR THREADING TECHNOLOGY

THREADING IS A BREEZE

- **Jet Air Threading Technology**

Thread the AIRFLOW 3000 with a blast of jet air. With threading ports that are connected to the end of each looper by tubes, at the press of a button, the air sends the thread through the looper. So, it's like a breath of fresh air to change thread colors.

- **Excellent Stitch Quality**

Excellent for fine knits and stretchy materials, which can be very challenging fabrics for a traditional sewing machine. Achieve outstanding finishing touches with flatlock, overlock, and rolled hem stitches on most specialty fabrics.

- **Quick Change Levers**

The AIRFLOW 3000 has pair of quick-change levers for the rolled hemstitch feature, and a switch that will activate and deactivate the cutting knife before the edge is wrapped with thread (overlocked).

- **Fast and Quiet**

The fast speeds of 1,300 stitches per minute make the AIRFLOW 3000 efficient. With the moderate noise level, you can add decorative touches and professional finishes to any DIY project, anywhere, anytime.

- **Differential Feed**

The Differential Feed Ratio (0.7mm to 2.0mm) provides outstanding stitch quality and acts as the tool for custom lettuce edge finishes on specialty materials.

- **Brightly Lit Work Area**

The AIRFLOW 3000 has plenty of high-quality LED lighting that is easy on the eyes when sewing on dark fabrics.

- **Included Accessories**

Blind stitch foot,
 Gathering foot
 Piping foot

Basic Features

Number of Threads	2/3/4
Needle Angle	Leaning
Sewing Speed (Stiches Per Minute)	1,300
Stitch Length	1-4mm
Differential Feed Ratio	0.7mm - 2.0mm
Overlock Seam Width	5mm - 7.5mm
Height of Presser Foot	5mm (Max. 6mm)
Presser Foot Adjustment	•
Air Threader	Electrical
Needle Threader	•
Thread Tension	Manual
Switch to Rolled Hemming Stitch	Built-in
Easy Change Dial for Thread Tension	•
Correction System of Needle Thread Tension	-
Fine Adjustment of Seam Width	-
Free Arm	-
Sensor of Front Cover	•
Sensor of Fabric Cover	•
Sensor of Presser Foot Up/Down	•
Error LED	•

Included Accessories

Trim Trap	•
Blind Stitch Foot	•
Gathering Foot	•
Piping Foot	•

KEY:

- Feature Included — Feature Not Included

AIRFLOW 3000 OVERLOCKER

Included Accessories and Accessory Feet

- Trim trap
- Needle set/ SCHMETZ130/705 80/12 :2pcs 90/14 :2pcs
- Spool cap : 4pcs
- Thread net : 4 pcs
- Hexagonal wrench(screw driver)
- Tweezers
- Cleaning brush
- Accessory BOX
- Soft cover
- Foot controller
- Treading wire
- Operation manual

Machine Specifications

- Gross info. (Carton)
50.2 x 50.5 x 48.7 (cm), 12.3Kg
- Net info. (machine only)
35.5 x 37.0 x 30.1 (cm), 9.6Kg



brother
at your side